

Documentation for CTS-Admin-Tool

Sascha Ludwig
saslugwi@uos.de

April 22, 2015

Contents

1	CTS-Iterator	2
1.1	Copy original files and init Java Eclipse Project	2
1.2	Installing Ruby	2
2	Tomcat7 and CTS Installation	2
3	Ruby and Sinatra	4
3.1	Ruby Sinatra Application to WAR-File	4
4	How to create a new entry in the menu bar	4
4.1	modification of /views/main.erb	5
4.2	modification in cts_admin_root.rb	6
4.3	creation of /views/admin_area.erb	7
4.4	optional: Javascripts	7
5	How to create a new entry in the CTS-action-bar	8
5.1	modification of /views/main.erb	9
5.2	modification in cts_admin_root.rb	9
5.3	creation of /views/myaction.erb	10
5.4	optional: Javascripts	11

1 CTS-Iterator

1.1 Copy original files and init Java Eclipse Project

- CTS Java-Iterator can be found here: <http://ctstest.informatik.uni-leipzig.de/>
- download the whole zip-File <https://bitbucket.org/jtiepmar/ctsiterator/downloads>
- unpack
- create new Java-Project in Eclipse
- copy files to the new Project Folder (rename source to src)
- in Eclipse, right click on the JDOM.jar and JDOM2.jar, "Build Path → Add"
- export as single .jar file

1.2 Installing Ruby

- for installing JRuby:
 - under Linux: see here: <https://rvm.io/>
 - some rvm commands:

```
rvm get stable
rvm list known
rvm list rubies
rvm install jruby
rvm install ruby
```

- under Windows: <http://jruby.org/download>
- installing missing gems with "gem install GEMNAME"
- calling Java methods in JRuby:
 - require 'java'
 - import NAMEOFCLASS
 - Java classes could now be used as in Java

2 Tomcat7 and CTS Installation

- under Windows use XAMPP
- install Oracle Java 8 on Ubuntu

```
sudo add-apt-repository ppa:webupd8team/java
sudo apt-get update
sudo apt-get install oracle-java8-installer oracle-java8-set-default
```

- installing Tomcat7 on Ubuntu System (there are errors with Tomcat8 though)

- **IMPORTANT: There must not be spaces in any paths !**

```
sudo apt-get install tomcat7 tomcat7-user
sudo apt-get install tomcat7-docs tomcat7-admin tomcat7-examples
```

- on Ubuntu, some directories are missing (ubuntu bug?!)

```
sudo mkdir /usr/share/tomcat7/common
sudo mkdir /usr/share/tomcat7/common/classes
sudo mkdir /usr/share/tomcat7/shared
sudo mkdir /usr/share/tomcat7/shared/classes
sudo mkdir /usr/share/tomcat7/server
sudo mkdir /usr/share/tomcat7/server/classes
```

- create a new, private Tomcat7 instance:

```
tomcat7-instance-create ctsadminsascha
```

- change ports; for config see: conf/server.xml
- add Oracle Java JDK in /bin/setenv.sh: JDK_DIRS="/usr/lib/jvm/java-8-oracle"
- see subfolder /logs for errors
- starting: /bin/startup.sh
- shutting down: /bin/shutdown.sh
- installing CTS-Iterator stuff:
- have a look at urncts.de
- start TomCat server
- copy cts.war to tomcat's "webapps" folder
- wait some time, maybe 15 seconds
- test successful installation by calling
`http://localhost:8080/cts/cts/?request=GetCapabilities`
- should return something like:
`<GetCapabilities><request>GetCapabilities</request><reply/></GetCapabilities>`
- configure MySQL access in /webapps/cts/WEB-INF/lib/conf.properties
- call inside /webapps/cts/WEB-INF/lib/ : `java -jar Datapreparation.jar`
- wait for some time for the program to finish
- check again by calling `http://localhost:8080/cts/cts/?request=GetCapabilities`

3 Ruby and Sinatra

installing required gems:

```
rvm use jruby
gem install warbler sinatra
```

or

```
rvm use jruby
bundle install
```

3.1 Ruby Sinatra Application to WAR-File

How to create a .war-file from the Ruby-Code

- Gemfile is needed (should be standard anyway)
- config.ru is needed for rake stuff
- call `jruby -S warble` in same directory where the ruby files are
- copy war-file to webapps folder
- it could not be used via the tomcat server (on errors, restart tomcat server)

Starting the Sinatra server without tomcat for development

- the Sinatra server is started by calling `rackup` in the root directory (= the directory where the config.ru is located)
- by default, the server binds to localhost:9292

4 How to create a new entry in the menu bar

- To create a new functionality that is not associated with an specific CTS-instance, the menu bar (= dark menu bar on top) is the right place
- to create a new tab there, 3 files have to be modified and 1 has to be created
 - `/views/main.erb` : [modify] this file is the main layout. This includes the menu bar (top), the side bar (left) and the cts-action-bar (beneath menu bar) but not the actual content
 - `cts_admin_root.rb` : [modify] this file handles all routes (= url calls) and the program logic. It also manages the connection to the database and OS stuff like file operations
 - `/views/admin_area.erb` : [create] this file will render the content specific to the new action
 - `/public/js/cts_admin.js` : [modify] this file handles the Javascript stuff, e.g. click on buttons and AJAX requests




Figure 1: general layout of the CTS-Admin-Tool

4.1 modification of /views/main.erb

- the menu bar is declared at the top of the page (`<nav class="navbar navbar-default navbar-fixed-top navbar-inverse">`). search here for the unordered list `<ul class="nav navbar-nav">`
- add a new entry to this list. e.g.

```
<li><a href="<%= url("/admin_area") %>">admin area</a></li>
```

- you should now see a new tab in the menu bar that points to `"/admin_area"`
- if you click on it, you will be redirected to the index page since the route `"admin_area"` does not exist (and default routing on 404 is the index page)
- note1: the `<%= %>` will run ruby code and inject the returned string directly into the html-code
- note2: the `'url()'` method will take a string and make an absolute path of it. this is necessary since tomcat runs not on the root but in a folder
- note3: always surround the ruby injections with double quotes. otherwise spaces can lead to strange html attributes

```

1▼ <nav class="navbar navbar-default navbar-fixed-top navbar-inverse">
2▼   <div class="container-fluid">
3     <!-- Brand and toggle get grouped for better mobile display -->
4▼     <div class="navbar-header">
5▼       <button type="button" class="navbar-toggle collapsed" data-toggle="collapse" data-target="#bs-example-navbar-collapse-1">
6         <span class="sr-only">Toggle navigation</span>
7         <span class="icon-bar"></span>
8         <span class="icon-bar"></span>
9         <span class="icon-bar"></span>
10      </button>
11      <a class="navbar-brand" href="<%= url("/") %>">CTS Admin Tool</a>
12    </div>
13
14    <!-- Collect the nav links, forms, and other content for toggling -->
15▼    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-1">
16▼      <ul class="nav navbar-nav">
17        <!-- <li class="active"><a href="#">Action One <span class="sr-only">(current)</span></a></li> -->
18        <li><a href="<%= url("/create_new_cts") %>">create new CTS</a></li>
19        <li><a href="<%= url("/update_template") %>">update CTS template</a></li>
20        <li><a href="<%= url("/admin_area") %>">admin area</a></li>
21        <li><a href="mailto:jtiepmar@informatik.uni-leipzig.de">contact J. Tiepmar</a></li>
22      </ul>
23
24▼      <ul class="nav navbar-nav navbar-right">
25        <p class="navbar-text">signed in as <span style="color:#5CB8E6"><strong><%= @current_user %></strong></span></p>
26        <li><a href="<%= url("/auth/logout") %>">logout</a></li>
27      </ul>
28    </div><!-- /.navbar-collapse -->
29  </div><!-- /.container-fluid -->
30 </nav>
31
32

```

Figure 2: step 1 in /views/main.erb

4.2 modification in cts_admin_root.rb

- now we have to create a route to handle the request for "/admin_area"
- this is done by adding another get-handler inside our Sinatra class in cts_admin_root.rb

```

# shows an administration area
get '/admin_area' do
  # needs authentication
  env['warden'].authenticate!
  # specific data
  @cts_file_marker = "CTSSStore.jar"
  # show stuff
  @sub_erb = :admin_area
  erb :main
end

```

- note1: if this page should be accessible without authentication, remove "env['warden'].authenticate!"
- note2: @sub_erb specifies the erb-file (default path in /views) that should be rendered in the content area
- note3: the last statement "erb :main" will return a html-string (from /views/main.erb) which will in turn be rendered inside the layout.erb (default by name convention) at the yield statement
- note4: the layout.erb only holds all css and java-script declarations as well as some meta-tags. this file is used for every request. whereas the main.erb is the second-level layout. It is mostly used but not for the login-screen.
- note5: thus, the render structure is: layout.erb → main.erb → @sub_erb (here: admin_area.erb)

```

375
376 # upload a new cts file
377 ▾ get '/update_template' do
378   # needs authentication
379   env['warden'].authenticate!
380   # data
381   @up_ret = nil
382   # show stuff
383   @sub_erb = :cts_upload_template
384   erb :main
385 end
386
387
388 # shows an administration area
389 ▾ get '/admin_area' do
390   # needs authentication
391   env['warden'].authenticate!
392
393   # specific data
394   @cts_file_marker = "CTSStore.jar"
395
396   # show stuff
397   @sub_erb = :admin_area
398   erb :main
399 end
400

```

Figure 3: step 2 in cts_admin_root.rb

4.3 creation of /views/admin_area.erb

- at this point, if we click on the menu-link to the admin area an error will occur since we have not created any file that hold our content
- thus, we have to create the file **/views/admin_area.erb** and fill it with some basic content

```

<h1>Admin Area</h1>

<p>file -marker: <%= @cts_file_marker %></p>

```

- the code is basically plain HTML with some extra ruby-features (erb = embedded ruby)
- the content of the variable `@cts_file_marker` will rendered in the paragraph-tag
- variables starting with an @ are instance variables. The scope of these variables is the current get or post-handler (that we have just created above). This includes the call of the erb-templates. Thus, all instance variables defined in the get/post-handler could be accessed
- after restarting the Sinatra server (STRG+C and then `rackup`) and going to the webadmin area we will see `file-marker: CTSStore.jar`

```

1 <h1>Admin Area</h1>
2
3 <p>file-marker: <%= @cts_file_marker %></p>

```

Figure 4: step 3 in /views/admin_area.erb

4.4 optional: Javascripts

- you could add your custom scripts at the end of the `/views/admin_area.erb` file

- or you could write it at the public/js/cts_admin.js

5 How to create a new entry in the CTS-action-bar

- To create a new functionality that is specific for an CTS-instance, the CTS-action-bar is the right place
- to create a new tab there, 3 files have to be modified and 1 has to be created
 - **/views/main.erb** : [modify] this file is the main layout. This includes the menu bar (top), the side bar (left) and the cts-action-bar (beneath menu bar) but not the actual content
 - **cts_admin_root.rb** : [modify] this file handles all routes (= url calls) and the program logic. It also manages the connection to the database and OS stuff like file operations
 - **/views/cts_myaction.erb** : [create] this file will render the content specific to the new action
 - **/public/js/cts_admin.js** : [modify] this file handles the Javascript stuff, e.g. click on buttons and AJAX requests





Figure 5: general layout of the CTS-Admin-Tool

5.1 modification of /views/main.erb

- go to the cts-action-bar part of the file (at the end) and find the `<ul class="nav nav-tabs nav-controlbar">`
- add another line

```
<li role="presentation" class=<%= "active" if @action == "myaction"%>>
<a href="<%= url("/forcts/#{@ctsname}/action/myaction") %>">Action</a>
</li>
```

- the "active" if @action == "myaction" ensures that the tab is marked as active when this action is selected (nicer design)
- the url for cts actions is built as follows: /forcts/CTSNAME/action/ACTIONNAME
- the action name should not contain spaces or any special characters



```
35 <!-- Sidebar and main content -->
36 <div class="container-fluid">
37 <div class="row">
38 <!-- The sidebar -->
39 <div class="sidebar col-sm-3 col-md-2 col-lg-2">
40 <p>list of all CTS:</p>
41 <ul class="nav nav-sidebar">
42 <% if @all_cts %>
43 <% @all_cts.each do |c| %>
44 <!-- Change default-tab here '? @action: "DEFAULT-ACTION"' -->
45 <li role="presentation" class=<%= "active" if @ctsname == c[:name] %> ><a href="<%= url("/forcts/#{c[:name]}/action/#{@action ? @action :
46 "db_config"}") %>"><%= c[:name] %></a></li>
47 <% end %>
48 </ul>
49 </div>
50
51 <!-- CTS-Action-Bar -->
52 <div class="main col-sm-9 col-sm-offset-3 col-md-10 col-md-offset-2 col-lg-10 col-lg-offset-2 ">
53 <div class="row">
54 <div class="controlbar col-sm-12 col-md-12 col-lg-12">
55 <ul class="nav nav-tabs nav-controlbar"> <!-- nav-justified -->
56 <li role="presentation" class=<%= "active" if @action == "db_config" %>><a href="<%= url("/forcts/#{@ctsname}/action/db_config") %>">
57 DB-Config</a></li>
58 <li role="presentation" class=<%= "active" if @action == "import" %>><a href="<%= url("/forcts/#{@ctsname}/action/import") %>">Data
59 Import</a></li>
60 <li role="presentation" class=<%= "active" if @action == "servlet" %>><a href="<%= url("/forcts/#{@ctsname}/action/servlet") %>">
61 Servlet</a></li>
62 <li role="presentation" class=<%= "active" if @action == "browse" %>><a href="<%= url("/forcts/#{@ctsname}/action/browse") %>">Browse
63 Data</a></li>
64 </ul>
65 </div>
66 </div>
67 <!-- Main Content -->
68 <div class="row main_content">
69 <% erb @sub_erb if @sub_erb %>
70 </div>
71 </div>
```

Figure 6: step 1 in /views/main.erb

5.2 modification in cts_admin_root.rb

- now we have to add this action to the action handler
- this is done by adding another if-branch inside the action handler in our Sinatra class in cts_admin_root.rb
- for that find `get '/forcts/*/action/*' do |ctsname, action|`
- add a new branch for your action:

```
elsif @action == "myaction"
  # return the current cts name in upper case
  @my_data = @ctsname.upcase
```

```
@sub_erb = :myaction # show my site
```

- note1: @sub_erb specifies the erb-file (default path in /views) that should be rendered in the content area
- note2: the last statement "erb :main" will return a html-string (from /views/main.erb) which will in turn be rendered inside the layout.erb (default by name convention) at the yield statement
- note3: the layout.erb only holds all css and java-script declarations as well as some meta-tags. this file is used for every request. whereas the main.erb is the second-level layout. It is mostly used but not for the login-screen.
- note4: thus, the render structure is: layout.erb → main.erb → @sub_erb (here: myaction.erb)

```
446 # fixed url to select collections and actions
447 # matches /collection/hello/action/world
448 # also possible instead of block: params[:splat] # => [hello, world]
449 get '/forcts/*/action/*' do |ctsname, action|
450   # needs authentication
451   env['warden'].authenticate!
452   # get parameter
453   @ctsname = ctsname
454   @action = action
455
456   # config tab
457   if get_all_cts().map{|e| e[:name] }.include?(ctsname)
458     if @action == "db_config"
459       # read the data base config part of the config file
460       @tbl_data = read_config_between("", "#IMPORT#", @ctsname)
461       @sub_erb = :cts_db_config # show the config site
462     elsif @action == "import"
463       # read the import settings and the log-files of recent import activities. also check if an import is currently running
464       @tbl_data = read_config_between("#IMPORT#", "#PARAMETERS#", @ctsname)
465       @import_runnig = File.exist?( @import_rubylock )
466       @log_lines = parse_ruby_logfile()
467       @sub_erb = :cts_import # show the import site
468     elsif @action == "servlet"
469       # read the servlet parameters
470       @tbl_data = read_config_between("#PARAMETERS#", "", @ctsname)
471       @sub_erb = :cts_servlet # show the servlet site
472     elsif @action == "myaction"
473       # return the cts name in upper case
474       @my_data = @ctsname.upcase
475       @sub_erb = :myaction # show my site
476     elsif @action == "browse"
477       @capa = "something went wrong"
478     begin
479       tc = tomcat_conf()
480       cts_url = "http://" + tc[:host] + ":" + tc[:port] + "/" + @ctsname + "/cts/?request=GetCapabilities"
481       site = Nokogiri::HTML( open( cts_url ).read )
482       @capa = CGI.escapeHTML(site.to_xml)
483     rescue
484       @capa = "CTS is not responding. #{cts_url}"
485     end
486     @sub_erb = :cts_browse # browse
487   else
488     @sub_erb = :index
489   end
490 else
491   @sub_erb = :index
492 end
493 # show
494 erb :main
495 end
```

Figure 7: step 2 in cts_admin_root.rb

5.3 creation of /views/myaction.erb

- this is similar to the creation as for the menu bar (see section above)

5.4 optional: Javascripts

- this is similar to the creation as for the menu bar (see section above)